

**Listing of the Claims:**

The following is a complete listing of all the claims in the application, with an indication of the status of each:

1. (Original) A method of handover from a first radio access technology to a second radio access technology for a mobile radio communications device within a mobile radio communications network, and including determining a timing advance value associated with the second radio access technology, the method characterized by employing positional data of the device within the network for determining the said timing advance value.
2. (Original) A method as claimed in claim 1, wherein the timing advance value is also determined on the basis of the location of the base station system associated with the second radio access technology.
3. (Previously presented) A method as claimed in claim 1, wherein the positional data of the device is determined prior to handover.
4. (Previously presented) A method as claimed in claim 1, wherein the timing advance value is determined within the network.
5. (Original) A method as claimed in claim 4, wherein the positional data is provided within a serving radio network controller of the network.
6. (Original) A method as claimed in claim 5, wherein the positional data is delivered by way of a core network arrangement to the basestation system.
7. (Previously presented) A method as claimed in claim 5, wherein the timing advance value is signalled to the device from the basestation system.

8. (Original) A method as claimed in claim 7, wherein the timing advance value is included within the handover command as received by the device.
9. (Previously presented) A method as claimed in claim 1, wherein the timing advance value is determined within the device.
10. (Original) A mobile communications system arranged for operation with a first radio access technology and a second radio access technology and including means for initiating the handover of a mobile radio communications device from the first radio access technology to the second radio access technology, wherein the means for initiating the handover including means for determining a timing advance value associated with the second radio access technology and wherein such means is arranged to employ positional data of the device within the network for determining the said timing advance value.
11. (Original) A system as claimed in claim 10, and arranged such that the timing advance value is also determined on the basis of the location of the basestation system associated with the second radio access technology.
12. (Previously presented) A system as claimed in claim 10, and arranged such that the positional data of the device is determined prior handover.
13. (Previously presented) A system as claimed in claim 10, and arranged such that the timing advance value is determined within the network
14. (Original) A system as claimed in claim 13, and arranged such that the positional data is provided within a serving radio network controller.
15. (Original) A system as claimed in claim 14, and arranged such that the positional data is delivered by way of a core network arrangement to the basestation system.

16. (Previously presented) A system as claimed in claim 13, and arranged for signalling the timing advance value to the device from the basestation system.

17. (Original) A system as claimed in claim 16, wherein the timing advance value is included within the handover command as received by the device.

18. (Previously presented) A system as claimed in claim 10, and arranged such that the timing advance value is determined within the device.

19-20. (Canceled)